

AKDO®

ALPINE

Organic. Classic. Warm
A timeless look meets timeless durability.

Far Beyond the Surface

Grey



Alpine 8" x 48" Grey (M)

PO2717-0848M0



Alpine Line 24" x 48" Grey (M)

PO2717-2448LN





Oak



Alpine 8" x 48" Oak (M)

PO2720-0848M0



Ceramic

Alpine Wall 12" x 36" Oak (M)

CR2720-1236WA

Redwood



Alpine 8" x 48" Redwood (M)

PO2718-0848M0



Alpine Line 24" x 48" Redwood (M)

PO2718-2448LN





Walnut



Alpine 8" x 48" Walnut (M)

PO2719-0848M0



Alpine Line 24" x 48" Walnut (M)

PO2719-2448LN

CONVERSION CHART

PROFILE	SIZE
8" x 48"	7.87" x 47.24"
24" x 48"	23.62" x 47.24"
12" x 36"	11.81" x 35.43"

APPLICATIONS — ALPINE & ALPINE LINE, PORCELAIN

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	Yes	Yes	No	Yes	Yes	No

BACKSPLASH	FIREPLACE SURROUND
Yes	Yes

TECHNICAL DATA

FEATURES	STANDARD TEST	SPECIFICATION
Bending Resistance	ISO 10545-4	MIN 35
Booted Ramp Test	DIN 51130 (Alpine Line)	R11
Breaking Strength	ISO 10545-4	MIN 1300
Frost Resistance	ISO 10545-12	Compliant
Pendulum Friction Test	UNE-ENV 12633 UNE 41901:2017 EX	Class C1
Reaction to Fire		A1 - A1fl
Regularity of Length & Width	ISO 10545-2	Compliant
Regularity of Rectangularity	ISO 10545-2	Compliant
Regularity of Straightness of Sides	ISO 10545-2	Compliant
Regularity of Surface Flatness	ISO 10545-2	Compliant
Regularity of Thickness	ISO 10545-2	Compliant
Resistance to High Concentrations of Acids and Alkalis	ISO 10545-13	MIN HB
Resistance to Household Chemicals	ISO 10545-13	MIN B
Resistance to Low Concentrations of Acids and Alkalis	ISO 10545-13	MIN LB
Resistance to Swimming Pool Salts	ISO 10545-13	MIN B
Stain Resistance	ISO 10545-14	Complies
Water Absorption	ISO 10545-3	≤0.5%

Due to the inherent characteristics of porcelain, there may be variations in color, movement and texture from lot to lot. For detailed installation guidelines, visit akdo.com.

APPLICATIONS — ALPINE WALL, CERAMIC

WALL	FLOOR	INTERIOR	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL
Yes	No	Yes	No	Yes	Yes	No

BACKSPLASH	FIREPLACE SURROUND
Yes	Yes

TECHNICAL DATA

FEATURES	STANDARD TEST	SPECIFICATION
Resistance to Cracking	UNE-EN ISO 10545-11	Compliant
Resistance to Thermal Shock	UNE-EN ISO 10545-9	Compliant
Frost Resistance	UNE-EN ISO 10545-12	Compliant
Resistance to High Concentrations of Acids and Alkalis	ISO 10545-13	MIN HB
Resistance to Household Chemicals	ISO 10545-13	MIN B
Resistance to Low Concentrations of Acids and Alkalis	ISO 10545-13	MIN LB
Resistance to Swimming Pool Salts	ISO 10545-13	MIN B
Reaction to Fire		A1 - A1fl

Due to the inherent characteristics of ceramic, there may be variations in color, movement and texture from lot to lot. For detailed installation guidelines, visit akdo.com.

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com

