



AKDO®

HEAR
IN

SONIK

*Industrial. Iridescent. Ingenious.
A modern take on metal.*

Far Beyond the Surface





Sonik 2'' x 2'' Black Mosaic (M)
PO2532-M002M0



Sonik 12'' x 24'' Black (M)
PO2532-1224M0



Sonik 24'' x 24'' Black (M)
PO2532-2424M0

SONIK

SONIK BRONZE



Sonik 2'' x 2'' Bronze Mosaic (M)
PO2531-M002M0



Sonik 12'' x 24'' Bronze (M)
PO2531-1224M0



Sonik 24'' x 24'' Bronze (M)
PO2531-2424M0







Sonik 2'' x 2'' Pearl Mosaic (M)
PO2529-M002M0



Sonik 12'' x 24'' Pearl (M)
PO2529-1224M0



Sonik 24'' x 24'' Pearl (M)
PO2529-2424M0

SONIK

SONIK SILVER



Sonik 2'' x 2'' Silver Mosaic (M)
PO2530-M002M0



Sonik 12'' x 24'' Silver (M)
PO2530-1224M0



Sonik 24'' x 24'' Silver (M)
PO2530-2424M0





CONVERSION CHART

PROFILE	SIZE
12" x 24"	11.81" x 23.62" = 1.937 sqft
24" x 24"	23.62" x 23.62" = 3.875 sqft

APPLICATIONS

WALL	FLOOR	TRAFFIC	EXTERIOR FREEZE/THAW	STEAM SHOWER	WET AREA	POOL	BACK- SPLASH	FIREPLACE SURROUND
Yes	Yes	Heavy Commercial	Yes	Yes	Yes	Yes	Yes	Yes

TECHNICAL DATA

FEATURES & STANDARD	SPECIFICATION
Abrasion Resistance - ISO 10545-6	≤150mm ³
Barefoot Ramp Test - DIN 51097	A
Bond Strength - EN 1348	≥1.0 N/mm ² (Class C2 - EN 12004)
Breaking Strength - ISO 10545-4	S ≥1500 N
DCOF - ANSI A.137.1	>.42
Frost Resistance - ISO 10545-12	Resistant
Impact Resistance - ISO 10545-5	≥0.55
Bending Resistance - ISO 10545-4	R ≥40 N/mm ²
Moisture Expansion - ISO 10545-10	≤0.01% (0.1mm/m)
Reaction to Fire - N/A	A1 - A1fl
Regularity of Length & Width - ISO 10545-2	Compliant
Regularity of Rectangularity - ISO 10545-2	Compliant
Regularity of Straightness of Sides - ISO 10545-2	Compliant
Regularity of Thickness - ISO 10545-2	Compliant
Resistance of High Concentrations of Acids and Alkalis - ISO 10545-13	HA
Resistance to Household Chemicals - ISO 10545-13	A
Resistance to Low Concentrations of Acids and Alkalis - ISO 10545-13	LA
Resistance To Staining - ISO 10545-14	5
Resistance to Swimming Pool Salts - ISO 10545-13	A
Booted Ramp Test - DIN 51130	R9
Surface Flatness - ISO 10545-2	Compliant
Thermal Shock Resistance - ISO 10545-9	Resistant
Water Absorption - ASTM C373	≤0.5%

AKDO

1435 State Street
Bridgeport, CT 06605
1.800.811.2536
203.336.5199 (o)
203.336.0603 (f)

AKDO NYC

22 West 21st Street
New York, NY 10010
1.800.811.2536
212.485.0448 (o)
212.485.0449 (f)

AKDO Pacific

3445 Arden Road
Hayward, CA 94545
1.888.909.2536
510.785.2536 (o)
510.785.0895 (f)

akdo.com